# StealthStat II Covert Traffic Statistics



# Discretely collect and easily analyze traffic data to identify and report speed related issues.

# Easy to Deploy

- Light weight compact design
- Simple install and setup
- Long lasting battery or solar option
- USB and wireless download
- Common mounting bracket with Kustom PMD

# Rugged, Reliable & Secure

- Lockable polycarbonate enclosure
- IP-68/NEMA 4 waterproof protection
- Kustom Signals Directional K-band radar

# **Effective Speed Studies**

- Collect and analyze traffic data
- Two+ lanes coverage (typical)
- Approaching, receding or both directions
- Free flow method replaces road tubes

# **Flexible Reporting Solutions**

- SMARTstat configuration & analysis software
- Auto report generation
- Compile tables and graphs of studies
- Deploy speed calming solutions
- Schedule targeted enforcement







Secure



Simple operation Approaching, receding or both

Traffic Data

## Discrete traffic analysis

Accurate, comprehensive data

## **Target enforcement**

Kustom Signals Inc. 9652 Loiret Boulevard, Lenexa, KS, 66219, USA.

#### www.KustomSignals.com

Tel. 800-458-7866 913-492-1400

# StealthStat II Covert Traffic Statistics

10.6"H x 8.6" W x 6.6"D (26.9 cm x 21.8 cm x 16.7 cm)

Polycarbonate, lockable

12V sealed lead acid

20 W, indefinite use

Free-flow method

1,000 ft. (300+ m.)

24.125 GHz  $\pm$  100 MHz Multilane 12° beamwidth

20 amp-hours

8 days (typical)

6.7 lbs. 20 lbs.

IP-68/NEMA 4 solid/liquid ingress

Kustom Signals Directional K-band

Approaching, receding, or both

-22° to +160°F (-30° to + 60° C)

105 ft wide at 500 ft (30m wide at 150m)



## **Specifications**

- Dimensions:
- Enclosure:
- Weight:
- w/ battery:
- Battery:
- Run Time:
- Solar option:
- RADAR:
- Lane coverage:
- Traffic Count:
- Direction:
- Typical range:
- Operating Temp:
- Speed accuracy:  $\pm 1 \text{ mph} (\pm 1 \text{ kph})$
- Data storage:
- 1/0:
- e: 4 MB USB and low powered wireless
- Mounting:
  - Pole mount bracket
  - Strap kit: 0.022" (0.56 mm) Worm-Drive hose & tube clamp
    Clamp ID: 2" to 12 ¼" (51 to 311 mm)

### Features

- Event scheduler for customized data collection
- Data Conversion of multiple traffic data file types
- Supports all versions MS Excel
- Simple, intuitive user interface
- Compile tables & graphs of studies
- Auto report generation
- Print & export charts for other software reporting

## Sample Charts




Chart: Volume - By Time




Chart: Speed - Maximum Speed



StealthStat - Data Sheet - USA Eng - Print - 09/2019

Kustom Signals Inc. 9652 Loiret Boulevard, Lenexa, KS, 66219, USA.

#### www.KustomSignals.com

Tel. 800-458-7866 913-492-1400